

TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:
MERB000025M
Revision no.:
5

This Certificate is issued by DNV UK Limited, UKAS accredited certification body no. 6086, based on authorisation of the Maritime & Coast Guard Agency (MCA) as an UK Approved Body (no. 0097) to undertake conformity assessments on marine equipment in accordance with the requirements of the Merchant Shipping (Marine Equipment) Regulations 2025.

This is to certify:

that the **Rate-of-turn indicator**

with type designation(s)
NAVIGAT 100, NAVIGAT 100M, NAVIGAT 200, NAVIGAT 2500 and NAVIGAT 3500

issued to

Sperry Marine B.V. - German Branch
Woltmanstr. 19 20097 Hamburg Germany,

is found to comply with the Regulation (UK) **MSN 1874 Amendment 11** for
Item no. **UK/4.9 (Row 2 of 2)**

according to the following requirements:

**SOLAS 74 Reg. V/19, IMO Res.A.526(13), IMO Res. A.694(17), IMO Res. MSC.191(79), IMO Res. MSC.302(87),
SOLAS 74 Reg. V/18, SOLAS 74 Reg. X/3, IMO Res. MSC.36(63)-(1994 HSC Code) 13, IMO Res. MSC.97(73)-(2000
HSC Code) 13**

Further details of the equipment and conditions for certification are given overleaf.

Date of issue: **2026-04-30**

Expiry date: **2031-04-29**

DNV local unit:
**Hamburg – CMC
North/East**

Approval Engineer:
Jörg Rebel



Approved Body No.: **0097**



for **DNV UK Ltd.**

Digitally Signed By:

Christine Mydlak-Röder

Christine Mydlak-Röder
MER Service Responsible



**Maritime &
Coastguard
Agency**

UK Approved Body Authorised
by the MCA

This certificate will not be valid if the manufacturer makes any changes or modifications to the approved type of equipment, which have not been notified to, and agreed with the approved body named on this certificate.

During the period of validity of this certificate the applicable regulations (international conventions and the relevant resolutions and circulars of the IMO) and testing standards may change, therefore the product conformity may need to be re-assessed by the Approved Body.

"The Mark of Conformity" may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-control phase module (D, E or F) of Schedule 2 of the Merchant Shipping (Marine Equipment) Regulations 2025, as amended is fully complied with and controlled by a written inspection agreement with an approved body. In case limitations of use apply, these should be indicated in the Annex.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Product description

Please see Appendix: Product Description

Application/Limitation

- The rate-of-turn indicator systems NAVIGAT 100, NAVIGAT 100M, NAVIGAT 200, NAVIGAT 2500 and NAVIGAT 3500 fulfil the carriage requirements according to 2000 HSC Code, 13.
- Installation to be performed according to manufacturer's Operation, Installation and Service manual.
- If no Control and Display Unit is connected, the Compass System must be connected to a Central Alert Management (CAM) system and to a back-up CAM system for alert management.

Type Examination documentation

Please see Appendix: Type Examination Documentation

Tests carried out

- Environmental and EMC testing: IEC 60945 (2002) incl. Corrigendum 1 (2008)
- Interface testing: IEC 61162-1 (2016) and IEC 61162-2 (1998)
- Presentation testing: IEC 62288 (2021) incl. Amendment 1 (2024)
- Bridge alert management testing: IEC 62923-1 (2018) and IEC 62923-2 (2018)
- Performance testing: ISO 20672 (2022)

Note: Further tests passed according to DNV Rules for Ships Pt.6 Ch.3 (July 2022), especially: 6.2.3.6 Dual heading input – NAUT(AW) and 6.3.1 Dual compass systems.

Marking of product

According to IEC 60945, Sect.4.9:

The product to be marked with following information, where practicable:

- Identification of the manufacturer,
- Equipment type number or model identification under which it was type tested,
- Serial number of the unit,
- Compass safe distance.

Alternatively, the marking may be presented on a display at equipment start-up, and in case of fixed equipment compass safe distance may be given in the equipment manual.

APPENDIX

Type Examination documentation

Certificate no.:
MERB000025M
 Revision no.:
5

Document No.	Rev.	Title
152-20	2	Report: TREO, Vibration tests acc. to ISO 8728, Clause 6.10.3
005026-0141-26	C	Report: NG Sperry Marine, Tests acc. to ISO 8728, ISO 20672 and ISO 16328
5017-0141-17	C	Report: NG Sperry Marine, Tests acc. to IEC 62923-1/-2 (2018)
5026-0141-27	C	Report: NG Sperry Marine, Tests acc. to test plan 5026-0113-01 Rev. A1 (K60)
5017-0141-20	A3	Report: NG Sperry Marine, Test summary acc. to IEC 60945, IEC 61162-1/-2 and IEC62288 (2021) for LPC54608
5017-0141-21	A3	Report: NG Sperry Marine, Interface tests acc. to IEC 61162-1 and IEC 61162 for LPC54608-2 (K60)
5017-0141-22	A2	Report: NG Sperry Marine, Software tests acc. to IEC 60945 for LPC54608
5039_5040-0141-05	A	Report: NG Sperry Marine, Test summary for NAVIGAT 2500/3500 with hardware modifications
5039_5040-0141-06	A	Report: NG Sperry Marine, Tests for NAVIGAT 2500/3500 acc. to ISO 20672 (2022)
5017-0141-24	A	Report: NG Sperry Marine, Regression tests for integration of NAVIGAT 2500/3500 into CompassNet
5017-0141-28	A	Report: NG Sperry Marine, Test summary for NAVIGAT 2500/3500
5017-0141-29	A1	Report: NG Sperry Marine, Sea trials for NAVIGAT 2500/3500 on MS ROBIN HOOD
5017-0141-30	A1	Report: NG Sperry Marine, Data gap analysis for NAVIGAT 2500/3500
5017-0141-31	A	Report: NG Sperry Marine, Integration tests for NAVIGAT 2500/3500 with CompassNet
5026-0141-04	A	Report: NG Sperry Marine, Tests for DDU (5017), CAU (5018), NAVITWIN V (5019) and NAVIGAT 200 acc. to IEC 60529 (IP 2x)
5026-0141-05	A	Report: NG Sperry Marine, Tests for DDU (5017), CAU (5018), NAVITWIN V (5019) and NAVIGAT 200 acc. to IEC 60945, 11.1
5026-0141-07	B	Report: NG Sperry Marine, Tests for NAVIGAT 100 acc. to IEC 61162-1, B.4.9.2 and B.4.12 for RMC, GGA, GLL and VTG (w/o 1st page)
5026-0141-07	B	Report: NG Sperry Marine, Tests for NAVIGAT 100 acc. to IEC 61162-1, B.4.9.2 and B.4.12 for RMC, GGA, GLL and VTG (1st page with signatures)
16-042	01	Report: BV, EMC tests for CAU (5018) acc. to IEC 60945, 9 and 10
16-045	01	Report: BV, EMC tests for NAVIGAT 100/200 acc. to IEC 60945, 9 and 10
002-16	1	Report: TREO, Tests for NAVIGAT 100 acc. to ISO 16328, 6.10.2, 6.10.5 and 6.10.6
003-16	1	Report: TREO, Tests for DDU (5017), CDU (5019) and CAU (5018) acc. to IEC 60945, 8.2 to 8.4 and 8.7
5017-0141-01	A1	Report: NG Sperry Marine, Tests for alignment of Hexapod table at Woltmannstr. 19, 20097 Hamburg, Germany
5017-0141-03	B	Report: NG Sperry Marine, Tests for CompassNet acc. to IEC 61162-1/-2 (1st page with signatures)

5019-0141-01	B1	Report: NG Sperry Marine, Tests for CompassNet CDU (5019) acc. to IEC 62288 (2014)
5026-0141-01	A	Report: NG Sperry Marine, Tests for NAVIGAT 100 acc. to ISO 16328 (2014), 6.2 to 6.6
5026-0141-02	B	Report: NG Sperry Marine, Tests for NAVIGAT 100 acc. to ISO 16328 (2014), 6.7
5026-0141-03	A	Report: NG Sperry Marine, Tests vor NAVIGAT 200 acc. to ISO 20672, 6.3
17-010	02	Report: BV, EMC tests acc. to IEC 60945, 9 and 10
5026-0141-08	B	Report: NG Sperry Marine, Tests for Gyro Container Mod. 10/4 acc. to ISO 8728 (2014), ISO 16328 (2014) and ISO 20672 (2007)
172-17	1	Report: TREO, Tests for NAVIGAT 100 with Container Mod.10/4 acc. to ISO 8728 (2014), 6.10.3.1 and ISO 16328 (2014), 6.10.4.1
5017-0141-03	B	Report: NG Sperry Marine, Tests for CompassNet acc. to IEC 61162-1/-2 (w/o 1st page)
5017-0141-39	A	Report: Sperry Marine, Summary of tests for integration of NG100 to CompassNet
5017-0141-40	A	Report: Sperry Marine, Tests for integration of NG100 to CompassNet
056373	H	Manual: Operation, installation and service of NAVIGAT 100
056374	J	Manual: Operation of NAVIGAT 200 / NAVIGAT 100M
056416	A	Manual: Installation and service of CompassNet
056417	A	Manual: Installation and service of NAVIGAT 200 / NAVIGAT 100M
5019-0141-02	A	Report: Sperry Marine, Tests for NAVITWIN V (P/N 074902-0002-000) acc. to IEC 62288 (2021)
5019-0141-03	A	Report: Sperry Marine, Tests for NAVITWIN V (P/N 074902-0002-000) acc. to IEC 60945, IEC 61162-1/-2, IEC 62288 (2021), IEC 62923-1/-2, ISO 8728, ISO 16328 and ISO 20672
056372	M	Manual: Operation of CompassNet
5017-0141-44	A	Report: Sperry Marine, Tests acc. to approved test plan 5017-0113-08 Rev. 01
056351	D	Manual: Operation, Installation and Service of Universal Digital Repeater
259-25	1	Report: TREO, Tests for NAVITWIN V (P/N 074902-0002-000) acc. to IEC 60945, 11.2
265-25	1	Report: TREO, Tests for NAVITWIN V (P/N 074902-0002-000) acc. to IEC 60945, 7, 8.2 and 8.4
F250787E1	2025-06-18	Report: Phoenix Testlab, Flicker test for NAVITWIN V (P/N 074902-0002-000) acc. to IEC 62288 (2021), 7.2.3



APPENDIX

Product Description

Certificate no.:
MERB000025M
Revision no.:
5

The rate-of-turn indicator systems NAVIGAT 100, NAVIGAT 100M and NAVIGAT 200 are based on spinning mass gyro compasses, NAVIGAT 2500 and NAVIGAT 3500 are based on fiber-optic gyro compasses. All compasses can be installed in single or multi-compass systems.

The following equipment is necessary for functioning:

Mandatory components:

NAVIGAT 100

Mastercompass NAVIGAT 100 P/N: 073518-0000-xxx
with
Gyrosphere: P/N: 074829-0000-xxx
or P/N: 074831-0000-xxx
and
Gyro Container Mod. 10/4 P/N: 025953-0000-xxx

NAVIGAT 100M

Mastercompass NAVIGAT 100 P/N: 073518-0000-xxx
with
Gyrosphere: P/N: 074829-0000-xxx
or P/N: 074831-0000-xxx
and
Gyro Container Mod. 10/4 P/N: 025953-0000-xxx
and
Ringbus Module P/N: 020771-0000-xxx
Data Distribution Unit P/N: 074907-0001-xxx
or P/N: 074907-0002-xxx

NAVIGAT 200

Mastercompass NAVIGAT 200 P/N: 073517-0000-xxx
with
Gyrosphere: P/N: 074829-0000-xxx
or P/N: 074831-0000-xxx
and
Gyro Container Mod. 10/4 P/N: 025953-0000-xxx
Data Distribution Unit P/N: 074907-0001-xxx
or P/N: 074907-0002-xxx

NAVIGAT 2500

Mastercompass NAVIGAT 2500 P/N: 073524-0000-xxx
or P/N: 073524-0001-xxx
Data Distribution Unit P/N: 074907-0001-xxx
or P/N: 074907-0002-xxx
Converter and Amplifier Board * P/N: 020760-0000-xxx

NAVIGAT 3500

Mastercompass NAVIGAT 3500 P/N: 073525-0000-xxx
or P/N: 073525-0001-xxx
Data Distribution Unit P/N: 074907-0001-xxx
or P/N: 074907-0002-xxx
Converter and Amplifier Board * P/N: 020760-0000-xxx

* Note: Converter and Amplifier Board may be part of the Data Distribution Unit (see above) or of a separate Converter and Amplifier Unit P/N: 074904-0000-xxx

One or more of the following rate-of-turn indicators to be used:

Rate-of-Turn indicator (in housing with bracket)	192 mm	Range ± 30 °/min	P/N: 060402-0000-xxx or P/N: 061009-0000-xxx
Rate-of-Turn indicator (console mounted)	192 mm	Range ± 30 °/min	P/N: 060372-0000-xxx or P/N: 061010-0000-xxx
Rate-of-Turn indicator (console mounted)	192 mm	Range ± 60 °/min	P/N: 060421-0000-xxx or P/N: 061013-0000-xxx
Rate-of-Turn indicator (console mounted)	192 mm	Range ± 90 °/min	P/N: 060379-0000-xxx or P/N: 061011-0000-xxx
Rate-of-Turn indicator (console mounted)	192 mm	Range ± 300 °/min	P/N: 060380-0000-xxx or P/N: 061012-0000-xxx
Rate-of-Turn indicator (console mounted)	144 mm	Range ± 30 °/min	P/N: 060368-0000-xxx or P/N: 061005-0000-xxx
Rate-of-Turn indicator (console mounted)	144 mm	Range ± 60 °/min	P/N: 060393-0000-xxx or P/N: 061008-0000-xxx
Rate-of-Turn indicator (console mounted)	144 mm	Range ± 90 °/min	P/N: 060369-0000-xxx or P/N: 061006-0000-xxx
Rate-of-Turn indicator (console mounted)	144 mm	Range ± 300 °/min	P/N: 060370-0000-xxx or P/N: 061007-0000-xxx

Optional components:

Control and Display Unit NAVITWIN V	P/N: 074902-0000-xxx or P/N: 074902-0001-xxx or P/N: 074902-0002-xxx
DDU Processor Module	P/N: 025786-0001-xxx or P/N: 025786-0002-xxx
RS422 Splitter Box	P/N: 074800-0000-xxx or P/N: 074850-0000-xxx
Voyage Data Printer	P/N: 074913-0000-xxx
Opto-isolator	P/N: 055555-0000-xxx
Power Supply (input 110/220/380 V AC, output 35 V DC)	P/N: 074031-0000-xxx
Power Supply (input 110/220/380 V AC, output 50 V DC)	P/N: 074032-0000-xxx
Power Supply (input 110/220/380 V AC, output 70 V DC)	P/N: 074033-0000-xxx
Terminal Box	P/N: 074859-0000-xxx
Universal Digital Repeater (console mounted) or Universal Digital Repeater (in housing with brackets) with Terminal Box	P/N: 074833-0000-xxx P/N: 074834-0000-xxx P/N: 074837-0000-xxx
Multifunctional NAV Data Repeater	P/N: SM-XDI192N
Multifunctional NAV Data Repeater optional with Serial I/O Module Serial I/O Module Analogue Extension Module	P/N: SM-XDI144N P/N: SM-XDI-NX1 P/N: SM-XDI-NX2 P/N: SM-XDI-AX1

Software versions:

NAVIGAT 100 (M)	Software Version 3.2.x CCU Software Version 3.2.x CSU
NAVIGAT 200	Software Version 3.2.x CCU Software Version 3.2.x CSU
NAVIGAT 2500 P/N 073524-0000-xxx	Software Version FW 2.82.x ($x \geq 23$)
NAVIGAT 2500 P/N 073524-0001-xxx	Software Version Pack 20.1.x ($x \geq 4$)



Certificate no.: **MERB000025M**
Revision no.: **5**

NAVIGAT 3500 P/N 073525-0000-xxx
NAVIGAT 3500 P/N 073525-0001-xxx

Software Version FW 2.82.x ($x \geq 23$)
Software Version Pack 20.1.x ($x \geq 4$)

Converter and Amplifier Unit
Converter and Amplifier Board
Data Distribution Unit
DDU Processor Module
NAVITWIN V

Software Version 3.2.x
Software Version 3.2.x
Software Version 3.2.x
Software Version 3.2.x
Software Version 3.2.x

Notes:

The Data Distribution Unit (DDU) can manage up to four gyro compasses connected into the CompassNet ring bus and one magnetic compass with dedicated connection to the DDU.

For multi compass systems, a Control and Display Unit NAVITWIN V is required and the DDU must be equipped with one additional DDU Processor Module to provide full system redundancy.

The DDU offers the possibility to connect the NAVISTAR THD-GNSS or any other type approved heading sources using the Converter and Amplifier Unit or Converter and Amplifier Board.

The redundant multi compass system provides heading source functionality and is compliant with the requirements of DNV Rules for Ships Pt.6 Ch.3 regarding distribution of heading information.